

M
Metric-10 Head



U
Universal Head



B
Bayonet Head



P
Hexagonal + Metric Head



Easy
Adjustment

Stable adjusters
Adjust the extended length of each section as per your needs
Last section foam filled for poles over 6 m according to IEC 60855
Reinforced fibreglass tube
Up to 12 m

INDOOR and OUTDOOR
Use in dry environment

Telescopic pole with two sections made of reinforced fibreglass tube Ø 37 and 32 mm with humidity-proof seals on each end, hand protector, grip, tip and M (Metric-10), U (Universal), B (Bayonet) or P (Hexagonal + Metric-10) head.
The length of each section can be adjusted as needed by means of an adjustment system with locking handles.

Mod. BMTS-15/45

- Length folded: 0.85 meters
- Length extended: 1.486 meters
- Working voltage: 45 kV (fully extended)
- INDOOR and OUTDOOR use in dry environment
- Weight: 0.75 Kg

Code	Ref.
615300	**BMTS-15/45M**
615301	**BMTS-15/45U**
615302	**BMTS-15/45B**
615303	**BMTS-15/45P**

Mod. BMTS-20/66

- Length folded: 1.10 meters
- Length extended: 1.986 meters
- Working voltage: 66 kV (fully extended)
- INDOOR and OUTDOOR use in dry environment
- Weight: 0.95 Kg

Code	Ref.
615310	**BMTS-20/66M**
615311	**BMTS-20/66U**
615312	**BMTS-20/66B**
615313	**BMTS-20/66P**

Mod. BMTS-30/132

- Length folded: 1.65 meters
- Length extended: 3 meters
- Working voltage: 132 kV (fully extended)
- INDOOR and OUTDOOR use in dry environment
- Weight: 1.35 Kg

Code	Ref.
615320	**BMTS-30/132M**
615321	**BMTS-30/132U**
615322	**BMTS-30/132B**
615323	**BMTS-30/132P**