
Connections / Bimetallic connectors

10401 TBE

Tinned aluminium cable lug

TBE cable lugs are manufactured from aluminium tubing with a purity of 99.5% or higher, featuring a tin-plated surface finish to improve electrical contact.
Neutral grease is applied internally to prevent aluminium oxidation.

Tube dimensions comply with DIN 46329 standard.





Code	Ref.	Section (mm²)	Dimensions (mm)					x 100	Bag	Box
			ØE	ØI	ØT	L	A			
115090	**TBE-16**	16	12.0	5.8	8.5	48.0	18.0	0.437	1	400
115100	**TBE-25**	25	12.0	6.8		50.0	18.0	0.860	1	300
115110	**TBE-35**	35	14.0	8.2		66.0	21.0	1.360	1	250
115120	**TBE-50**	50	16.0	9.8	13.0	68.0	25.0	1.880	1	200
115130	**TBE-70**	70	18.5	11.2		84.0	28.0	2.700	1	200
115140	**TBE-95**	95	22.0	13.2		87.0	32.0	3.880	1	150
115150	**TBE-120**	120	23.0	14.7		88.0	32.0	5.600	1	100
115160	**TBE-150**	150	25.0	16.5		101.0	35.0	8.200	1	75
115170	**TBE-185**	185	28.5	18.5		103.0	40.0	10.600	1	50
115180	**TBE-240**	240	32.0	21.3	15.0	114.0	45.0	17.200	1	50
115190	**TBE-300**	300	34.0	23.6		120.0	49.0	20.700	1	40