
Metric Cable Gland Polyamide IP-68 Dark Gray





Material

Bonnet	Polyamide PA6 V2
Sealing gasket	POS
Body	Polyamide PA6 V2
O-ring	NBR
Thread Type	Metric (EN 60423)
Tightness	IP68 – 5 bar
Continuous working temperature	-20 ºC +100 ºC

Properties

Anti-vibration
High UV resistance
Easy assembly
VDE certificate (40030037)
Free of halogens
Short-term working temperature: -30 ºC+150 ºC

Product description

A stuffing box is a piece that allows a compression seal to be made at one end while ensuring the connection to the other end using a male thread.

Cable glands offer a great diversity of properties, whether mechanical, chemical or performance. The cable glands are quick to assemble and easy to install. They have a wide working temperature range.

Mechanically, they withstand and absorb any type of pull, vibration and shock.

The cable gland is present in any type of installation, machinery or equipment that requires a continuous electrical supply and is responsible for ensuring its connection.

Thread	Code	Hmm	GL mm	mm	mm
M 12 X 1.5	OMRG 01	24	8	15	3-65
M 16 X 1.5	OMRG 02	28	8	19	4-8
M 16 X 1.5	OMRG 03	29	10	22	5-10
M 20 X 1.5	OMRG 04RS	29	10	24	4-10
M 20 X 1.5	OMRG 04	29	10	24	6-12
M 25 X 1.5	OMRG 05	33	10	27	10-14
M 25 X 1.5	OMRG 06	38	10	33	13-18
M 32 X 1.5	OMRG 07	41	10	42	18-25
M 40 X 1.5	OMRG 08	51	10	53	22-32
M 50 X 1.5	OMRG 09	53	18	60	30-38
M 63 X 1.5	OMRG 10	55	18	70	33-44